

This safety data sheet complies with the requirements of: (CLP) Regulation (EC 1272/2008)

Revision Date 02-Apr-2021

Version 3

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code 58, 58QT
Product Name AUTO MAGIC LEATHER CONDITIONER
Unique Formula Identifier (UFI) Code WE94-D0EE-H00T-S8NX, WE94-D0EE-H00T-S8NX
Contains Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent), Distillates (petroleum), hydrotreated light

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Automotive Care Product; Leather conditioner. For professional use only.
Uses advised against Uses other than recommended use.

1.3. Details of the supplier of the safety data sheet

Manufacturer

ITW Evercoat
6600 Cornell Road
Cincinnati, Ohio 45242
Telephone: 513-489-7600

E-mail address:

Info@automagic.com

1.4. Emergency telephone number

24-hour emergency phone number - CHEMTREC: 1-800-424-9300 INTERNATIONAL: 1-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION:

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration toxicity	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Full text of R-phrases: see section 16

2.2. Label elements

Contains Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent), Distillates (petroleum), hydrotreated light



Signal word

Danger

Statements of hazard

H304 - May be fatal if swallowed and enters airways

H226 - Flammable liquid and vapor

Precautionary Statements

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment

P242 - Use only non-sparking tools

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

P370 + P378 - In case of fire: Use .? to extinguish

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to industrial incineration plant

Take precautionary measures against static discharge

Other Information

- Not applicable

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**Mixtures**

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent)	265-150-3	64742-48-9	10 - 30	Asp. Tox. 1 (H304)	01-2119467170-45-XXXX
Distillates (petroleum), hydrotreated light	265-149-8	64742-47-8	7 - 13	Asp. Tox. 1 (H304)	01-2119456620-43-XXXX
Isopropanol, 2-propanol	200-661-7	67-63-0	0.1 - 1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	01-2119457558-25-XXXX
Mineral Spirits (Stoddard Solvent)	232-489-3	8052-41-3	0.1 - 1	STOT RE 1 (H372) Asp. Tox. 1 (H304)	Exempt - Volume
ETHANOL, 2,2'-IMINOBIIS-	203-868-0	111-42-2	0.1 - 1	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT RE 2 (H373)	Exempt - Volume
Methanol	200-659-6	67-56-1	<0.1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	01-2119433307-44-XXXX
Polyethylene Glycol	500-039-8	25322-68-3	<0.1		01-2119457556-29-XXXX
Ethyl Benzene	202-849-4	100-41-4	<0.1	Acute Tox. 4 (H332) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)	Exempt - Volume
Cumene	202-704-5	98-82-8	<0.1	STOT SE 3 (H335) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226)	Exempt - Volume
5-Chloro-2-methyl-4-isothiazolin-3-one	247-500-7	26172-55-4	<0.1		Exempt -
Methyl-4-isothiazolin-3-one	220-239-6	2682-20-4	<0.1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330)	No Data Available

				Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) (EUH071) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	
Copper (II) nitrate	221-838-5	3251-23-8	<0.1		Exempt -

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	If symptoms persist, call a physician.
Inhalation	Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.
Skin contact	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.
Self-protection of the first aider	Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	See section 2 for more information
-----------------	------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Use. Use dry chemical. Carbon dioxide (CO₂). Water spray (fog). Alcohol resistant foam.

Unsuitable extinguishing media

No information available

5.2. Special hazards arising from the substance or mixture

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE**7.1. Precautions for safe handling****Advice on safe handling**

Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

Incompatible materials

Strong oxidizing agents

7.3. Specific end use(s)**Specific use(s)**

Automotive Care Product.

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Isopropanol, 2-propanol 67-63-0	-	TWA: 400 ppm TWA: 999 mg/m ³ STEL: 500 ppm STEL: 1250 mg/m ³	STEL: 400 ppm STEL: 980 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ STEL: 400 ppm STEL: 1000 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³
ETHANOL, 2,2'-IMINOBIS- 111-42-2	-	-	TWA: 3 ppm TWA: 15 mg/m ³	TWA: 0.46 ppm TWA: 2 mg/m ³ vía dérmica*	TWA: 0.11 ppm TWA: 0.5 mg/m ³ H*
Methanol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 100 ppm

67-56-1	TWA: 260 mg/m³ *	TWA: 266 mg/m³ STEL: 250 ppm STEL: 333 mg/m³ Sk*	TWA: 260 mg/m³ STEL: 1000 ppm STEL: 1300 mg/m³ *	TWA: 266 mg/m³ vía dérmica*	TWA: 130 mg/m³ H*	
Polyethylene Glycol 25322-68-3	-	-	-	-	TWA: 200 mg/m³ TWA: 1000 mg/m³	
Ethyl Benzene 100-41-4	TWA 100 ppm TWA 442 mg/m³ STEL 200 ppm STEL 884 mg/m³ *	TWA: 100 ppm TWA: 441 mg/m³ STEL: 125 ppm STEL: 552 mg/m³ Sk*	TWA: 20 ppm TWA: 88.4 mg/m³ TWA: 1000 mg/m³ STEL: 100 ppm STEL: 442 mg/m³ STEL: 1500 mg/m³ *	TWA: 100 ppm TWA: 441 mg/m³ STEL: 200 ppm STEL: 884 mg/m³ vía dérmica*	TWA: 20 ppm TWA: 88 mg/m³ H*	
Cumene 98-82-8	TWA 20 ppm TWA 100 mg/m³ STEL 50 ppm STEL 250 mg/m³ *	TWA: 25 ppm TWA: 125 mg/m³ STEL: 50 ppm STEL: 250 mg/m³ Sk*	TWA: 20 ppm TWA: 100 mg/m³ TWA: 150 mg/m³ TWA: 1000 mg/m³ STEL: 50 ppm STEL: 250 mg/m³ STEL: 1500 mg/m³ *	TWA: 20 ppm TWA: 100 mg/m³ STEL: 50 ppm STEL: 250 mg/m³ vía dérmica*	TWA: 10 ppm TWA: 50 mg/m³ H*	
Copper (II) nitrate 3251-23-8	-	-	-	TWA: 0.1 mg/m³	-	
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark	
Isopropanol, 2-propanol 67-63-0	-	TWA: 200 ppm STEL: 400 ppm	-	TWA: 200 ppm TWA: 500 mg/m³ STEL: 250 ppm STEL: 620 mg/m³	TWA: 200 ppm TWA: 490 mg/m³	
Mineral Spirits (Stoddard Solvent) 8052-41-3	-	TWA: 100 ppm	-	-	TWA: 25 ppm TWA: 145 mg/m³	
ETHANOL, 2,2'-IMINOBIS- 111-42-2	-	TWA: 1 mg/m³ P*	-	TWA: 0.46 ppm TWA: 2 mg/m³ iho*	TWA: 0.46 ppm TWA: 2 mg/m³ H*	
Methanol 67-56-1	TWA: 200 ppm TWA: 260 mg/m³ pelle*	TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm P*	TWA: 133 mg/m³ H*	TWA: 200 ppm TWA: 270 mg/m³ STEL: 250 ppm STEL: 330 mg/m³ iho*	TWA: 200 ppm TWA: 260 mg/m³ H*	
Polyethylene Glycol 25322-68-3	-	-	-	-	TWA: 1000 mg/m³	
Ethyl Benzene 100-41-4	TWA: 100 ppm TWA: 442 mg/m³ STEL: 200 ppm STEL: 884 mg/m³ pelle*	TWA: 100 ppm TWA: 442 mg/m³ STEL: 200 ppm STEL: 884 mg/m³ P*	TWA: 215 mg/m³ STEL: 430 mg/m³ H*	TWA: 50 ppm TWA: 220 mg/m³ STEL: 200 ppm STEL: 880 mg/m³ iho*	TWA: 50 ppm TWA: 217 mg/m³ H*	
Cumene 98-82-8	TWA: 20 ppm TWA: 100 mg/m³ STEL: 50 ppm STEL: 250 mg/m³ pelle*	TWA: 20 ppm TWA: 100 mg/m³ STEL: 50 ppm STEL: 250 mg/m³ P*	TWA: 100 mg/m³ STEL: 250 mg/m³ H*	TWA: 20 ppm TWA: 100 mg/m³ STEL: 50 ppm STEL: 250 mg/m³ iho*	TWA: 20 ppm TWA: 100 mg/m³ H*	
Copper (II) nitrate 3251-23-8	-	-	TWA: 0.1 mg/m³	TWA: 0.02 mg/m³	-	
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland	Slovenia
Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent) 64742-48-9	-	TWA: 50 ppm TWA: 300 mg/m³ STEL: 100 ppm STEL: 600 mg/m³	STEL: 900 mg/m³ TWA: 300 mg/m³	-	-	
Distillates (petroleum), hydrotreated light 64742-47-8	-	TWA: 50 ppm TWA: 350 mg/m³ TWA: 5 mg/m³ STEL: 100 ppm STEL: 700 mg/m³	-	-	-	
Isopropanol, 2-propanol 67-63-0	TWA: 200 ppm TWA: 500 mg/m³ STEL 800 ppm STEL 2000 mg/m³	TWA: 200 ppm TWA: 500 mg/m³ STEL: 400 ppm STEL: 1000 mg/m³	STEL: 1200 mg/m³ TWA: 900 mg/m³	TWA: 100 ppm TWA: 245 mg/m³ STEL: 125 ppm STEL: 306.25 mg/m³	TWA: 200 ppm STEL: 400 ppm Sk*	TWA: 200 ppm TWA: 500 mg/m³ 400: STEL ppm 1000: STEL mg/m³
Mineral Spirits (Stoddard Solvent) 8052-41-3	-	-	STEL: 900 mg/m³ TWA: 300 mg/m³	-	TWA: 100 ppm TWA: 573 mg/m³	

ETHANOL, 2,2'-IMINOBIS- 111-42-2	TWA: 0.46 ppm TWA: 2 mg/m ³ STEL 0.92 ppm STEL 4 mg/m ³ H*	TWA: 1 mg/m ³ STEL: 1 mg/m ³ H*	TWA: 9 mg/m ³	TWA: 3 ppm TWA: 15 mg/m ³ STEL: 6 ppm STEL: 22.5 mg/m ³	TWA: 0.2 ppm TWA: 1 mg/m ³ STEL: 0.6 ppm STEL: 3 mg/m ³ Sk*	TWA: 0.5 mg/m ³ TWA: 0.11 ppm 0.11: STEL ppm 0.5: STEL mg/m ³ K*
Methanol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ STEL 800 ppm STEL 1040 mg/m ³ H*	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 800 ppm STEL: 1040 mg/m ³ H*	STEL: 300 mg/m ³ TWA: 100 mg/m ³	TWA: 100 ppm TWA: 130 mg/m ³ STEL: 125 ppm STEL: 162.5 mg/m ³ H*	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 260 mg/m ³ 800: STEL ppm 1040: STEL mg/m ³ K*
Polyethylene Glycol 25322-68-3	TWA: 1000 mg/m ³ STEL 4000 mg/m ³	TWA: 1000 mg/m ³	-	-	-	TWA: 1000 mg/m ³ 8000: STEL mg/m ³
Ethyl Benzene 100-41-4	TWA: 100 ppm TWA: 440 mg/m ³ STEL 200 ppm STEL 880 mg/m ³ H*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 50 ppm STEL: 220 mg/m ³ H*	STEL: 400 mg/m ³ TWA: 200 mg/m ³	TWA: 5 ppm TWA: 20 mg/m ³ STEL: 10 ppm STEL: 30 mg/m ³ H*	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ Sk*	TWA: 100 ppm TWA: 442 mg/m ³ 200: STEL ppm 884: STEL mg/m ³ K*
Cumene 98-82-8	TWA: 20 ppm TWA: 100 mg/m ³ STEL 50 ppm STEL 250 mg/m ³ H*	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 80 ppm STEL: 400 mg/m ³ H*	STEL: 250 mg/m ³ TWA: 50 mg/m ³	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 50 ppm STEL: 250 mg/m ³ H*	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 50 ppm STEL: 250 mg/m ³ Sk*	TWA: 20 ppm TWA: 100 mg/m ³ 50: STEL ppm 250: STEL mg/m ³ K*
5-Chloro-2-methyl-4-isothiazolin-3-one 26172-55-4	TWA: 0.05 mg/m ³	TWA: 0.2 mg/m ³ STEL: 0.4 mg/m ³	-	-	-	
Methyl-4-isothiazolin-3-one 2682-20-4	TWA: 0.05 mg/m ³	TWA: 0.2 mg/m ³ STEL: 0.4 mg/m ³	-	-	-	
Copper (II) nitrate 3251-23-8	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³ STEL 4 mg/m ³ STEL 0.4 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³	TWA: 0.2 mg/m ³	-	-	

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Isopropanol, 2-propanol 67-63-0	-	-	-	40	25 mg/L
Methanol 67-56-1	-	-	-	15	15 mg/L
Ethyl Benzene 100-41-4	-	-	-	700	250 mg/g Creatinine
Cumene 98-82-8	-	-	-	-	10 mg/g Creatinine
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
Ethyl Benzene 100-41-4	-	-	-	5.2	-
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Isopropanol, 2-propanol 67-63-0	-	25	-	-	-
Methanol 67-56-1	-	30	-	-	-
Ethyl Benzene 100-41-4	-	600	-	-	-
Cumene 98-82-8	-	20	-	-	-

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls

Use exhaust ventilation to keep airborne concentrations below exposure limits.

Personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Suitable protective clothing. Wear chemical resistant clothing such as gloves, apron, boots or whole bodysuits made from neoprene, as appropriate. Antistatic footwear. Gloves made of plastic or rubber.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

Environmental exposure controls

Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	White
Odor	Leather
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	52 °C / 126 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.91	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

9.2. Other information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	0.9913
Density	No information available
Bulk density	No information available

Section 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Not applicable

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Carbon oxides

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

Inhalation	May cause irritation of respiratory tract.
Eye contact	Irritating to eyes. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. Prolonged contact may cause redness and irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	20,332.40 mg/kg
ATEmix (dermal)	9,489.60 mg/kg
<u>Unknown acute toxicity</u>	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropanol, 2-propanol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
ETHANOL, 2,2'-IMINOBIIS-	= 780 mg/kg (Rat)	= 11.9 mL/kg (Rabbit)	
2,6-Xylenol	= 296 mg/kg (Rat)	= 1 g/kg (Rabbit)	
Methanol	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
Cumene	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h
Ethyl Benzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Copper (II) nitrate	= 794 mg/kg (Rat)		

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target Organ Effects	Respiratory system, Eyes, Skin.
Aspiration hazard:	No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent)	-	2200: 96 h Pimephales promelas mg/L LC50	-
Distillates (petroleum), hydrotreated light	-	2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through	-
Isopropanol, 2-propanol	1000: 72 h Desmodesmus subspicatus mg/L EC50 1000: 96 h Desmodesmus subspicatus mg/L EC50	11130: 96 h Pimephales promelas mg/L LC50 static 9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
ETHANOL, 2,2'-IMINOBIS-	2.1 - 2.3: 96 h Pseudokirchneriella subcapitata mg/L EC50 7.8: 72 h Desmodesmus subspicatus mg/L EC50	1200 - 1580: 96 h Pimephales promelas mg/L LC50 static 4460 - 4980: 96 h Pimephales promelas mg/L LC50 flow-through 600 - 1000: 96 h Lepomis macrochirus mg/L LC50 static	55: 48 h Daphnia magna mg/L EC50
Methanol	-	13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static	-
Ethyl Benzene	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Cumene	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50
5-Chloro-2-methyl-4-isothiazolin-3-one	0.03 - 0.13: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.11 - 0.16: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	1.6: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	0.12 - 0.3: 48 h Daphnia magna mg/L EC50 Flow through 0.71 - 0.99: 48 h Daphnia magna mg/L EC50 Static 4.71: 48 h Daphnia magna mg/L EC50

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	Partition coefficient
Isopropanol, 2-propanol	0.05
ETHANOL, 2,2'-IMINOBIS-	-2.18
Methanol	-0.77
Ethyl Benzene	3.2
Cumene	3.7
5-Chloro-2-methyl-4-isothiazolin-3-one	-0.71 - 0.75

12.4. Mobility in soil**Mobility in soil**

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

None known.

Section 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Waste from residues/unused products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
Waste codes / waste designations according to EWC / AVV	No Data Available
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

Note:	This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.
--------------	---

IMDG

14.1 UN/ID No	UN1993
14.2 Proper shipping name	Flammable liquids, n.o.s (Hydrotreated Naphtha, Heavy)
14.3 Hazard Class	3
14.4 Packing Group	III
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 EmS-No	Not applicable

RID

14.1 UN/ID No	No information available.
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 Classification code	No information available

ADR

14.1 UN/ID No	No information available.
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated

14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 Classification code	No information available

IATA

14.1 UN/ID No	UN1993
14.2 Proper shipping name	Flammable liquids, n.o.s, (Hydrotreated Naphtha, Heavy)
14.3 Hazard Class	3
14.4 Packing Group	III
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 ERG Code	Not applicable

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent) 64742-48-9	RG 84	-
Distillates (petroleum), hydrotreated light 64742-47-8	RG 84	-
Isopropanol, 2-propanol 67-63-0	RG 84	-
Mineral Spirits (Stoddard Solvent) 8052-41-3	RG 84	-
ETHANOL, 2,2'-IMINOBIS- 111-42-2	RG 49, RG 49bis	-
Methanol 67-56-1	RG 84	-
Ethyl Benzene 100-41-4	RG 84	-
Cumene 98-82-8	RG 84	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical Name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
Hydrotreated Naphtha, Heavy (Mineral Spirits, Stoddard Solvent) - 64742-48-9	Use restricted. See item 28. Use restricted. See item 29.	
Mineral Spirits (Stoddard Solvent) - 8052-41-3	Use restricted. See item 28. Use restricted. See item 29.	
Methanol - 67-56-1	Use restricted. See item 69.	

Persistent Organic Pollutants

Not applicable

Chemical Name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methanol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Not determined
IECSC	Complies
KECL	Not determined
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION**Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

EUH071 - Corrosive to the respiratory tract
 H225 - Highly flammable liquid and vapor
 H226 - Flammable liquid and vapor
 H301 - Toxic if swallowed
 H302 - Harmful if swallowed
 H304 - May be fatal if swallowed and enters airways
 H311 - Toxic in contact with skin
 H314 - Causes severe skin burns and eye damage
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H318 - Causes serious eye damage
 H319 - Causes serious eye irritation
 H330 - Fatal if inhaled
 H331 - Toxic if inhaled
 H332 - Harmful if inhaled
 H335 - May cause respiratory irritation
 H336 - May cause drowsiness or dizziness
 H370 - Causes damage to organs
 H372 - Causes damage to organs through prolonged or repeated exposure
 H373 - May cause damage to organs through prolonged or repeated exposure
 H400 - Very toxic to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects
 H411 - Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorization:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Revision Date 02-Apr-2021

Revision Note Not applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet